Features



 Simply by adding to your speaker system, enjoy streaming music or a full MusicCast (multi-room audio) system. Compatible with all types of music sources and services, such as streaming services. MusicCast App for easy operation. The app lets you control other MusicCast-compatible components. One Push Play — Pressing any button turns the unit on and initiates playback of the previously selected source. Retro Modern & Superior Quality 48-bit digital volume control is far greater than the input signal bit resolution, achieving high quality control. Compact body only 214mm wide fits in any convenient location, can be used horizontally or vertically. Easy Installation - Suitable Size for 1U Rack with a width of 214mm and height of 42mm (without feet). Low standby power consumption: 1.92 W

Specifications

WXA-50

Wireless Streaming Amplifier





Output Power

Rated Output Power

 70 W per channel
 (6 ohms, 20Hz - 20kHz, 0.06% THD, 2 ch driven)

 90 W per channel
 (6 ohms, 1kHz, 0.9% THD, 1 ch driven)

Maximum Effective Output Power

 165 W per channel
 (4 ohms, 1kHz, 10% THD, 1 ch driven)

 110 W per channel
 (6 ohms, 1kHz, 10% THD, 1 ch driven)

 85 W per channel
 (8 ohms, 1kHz, 10% THD, 1 ch driven)

Audio Section			Dimensions (W x H x D)	
Total Harmonic Distortion		0.02 % THD (SP out [20 Hz-20 kHz])	214 x 51.5 (without leg:42) x 251.4 mm	
Frequency Response	Pre C	ut Optical / NET / USB: 10-100 kHz (± 0 / -3 dB)	(with antenna up: 214 x 123.6 (without leg:114.2) x 251.4 mm)	
	Pre C	ut AUX: 20-40 kHz (± 0 / -3 dB)	8-3/8" x 20-1/4" (without leg:1-5/8") x 9-7/8" mm	
	SP O	ut Optical / NET / USB: 10-50 kHz (± 0 / -3 dB)	(with antenna up: 8-3/8" x 4-7/8" (without leg:4-1/2") x 9-7/8" mm)	
	SP O	ut AUX: 20-40 kHz (± 0 / -3 dB)		
S/N Ratio (IHF-A)		104 dB	Weight	
				1.9 kg; 4.3 lbs.
Network Section				
Network		LAN (DLNA ver. 1.5 (DMR), Wi-Fi	Terminals	
Supported Format	MP3, WMA, MP	EG4 AAC 48 kHz / 24bit WAV, FLAC, AIFF 192 kHz / 24bit	Inputs	
		ALAC 96 kHz / 24 bit DSD 5.6 MHz	Network (Ethernet / Wi-Fi)	1/1
Bluetooth	(Versi	on) 2.1 + EDR (Supported Profile) A2DP, AVRCP	USB	1
	(Cc	mpatible Codec) Sink: SBC/AAC, Source: SBC	Optical Digital (32 kHz-192 kHz)	1
			Analogue Audio	1
Standby Power Consumption				
Network Standby off, Bluetooth Standby off		0.12 W	Outputs	
Network Standby on, Bluetooth Standby off		1.8 W (wired) / 1.68 W (wireless)	Speaker	2 ch
Network Standby on, Bluetooth Standby on		1.8 W (wired) / 1.92 W (wireless)	Subwoofer	1
Power Consumption				
		15 W (no signal condition)	Others	
			Remote In	1
			Trigger In / Out	1/1